

R5

Ribbon to Ribbon

BENEFITS AND FEATURES

- Remote Maintenance via Internet.
- Integrated 5 Function in One Unit (Stripping, Cleaning, Cleaving, Splicing, Protecting).
- The fusion splicer with All-In-One™ system provides the best workability.
- No scratches on fiber by thermal stripping.
- 4.3-inch Color LCD Monitor with Touch Screen & Bidirectional Operation System.
- Powerful Lithium Polymer Battery with Large Capacity.
- Resistance to Shock, Dust and Water.
- Built-in Dual Sleeve Heater.
- Equipped with Sleeve Loader easy fiber loading for ribbon fiber.




ALL IN ONE



MPO SOC




STRIPPING



CLEAVING



CLEANING



Ribbonizing Holder Kit

SPECIFICATION

CATEGORY	DESCRIPTION
Fiber alignment	Fixed V-Groove(Clad to Clad)
Applicable type of fibers	SM(ITU-T G.652), MM(ITU-T G.651), DS(ITU-T G.653), NZDS(ITU-T G.655), ITU-T(G.657)
Fiber count	Single fiber, 2~12 fiber
Applicable fiber dimensions	Single: Cladding diameter 125µm, Coating diameter 250, 900µm Ribbon: Cladding diameter 125µm, Ribbon fiber thickness 0.27 to 0.32mm
Fiber setting and cleaved length	8mm
Splicing modes	Splice mode: 100, Heat mode: 50
Typical splice Loss	SM: 0.05dB, MM: 0.02dB, DS: 0.08dB, NZDS: 0.08dB
Return loss	> 60dB
Splicing time	Typical 20sec with standard SM(ITU-T G.652)
Splice loss estimate	Available
Sleeve heating time	30sec, 50sec
Applicable protection sleeve	40, 60mm(fiber)
Storage of splice result	The last 10,000 results to be stored in the internal memory.(Image 10,000 results)
Tension test	2N / 4,4N(Option)
Operating condition	Altitude: 5,000m above sea level, Temperature: - 10°C~50°C ,Humidity: 0~95%, Wind: 15m/s, non-condensing, dust proof, water proof, shock proof
Storage condition	Temperature: -40°C ~80°C, Humidity: 0~95%
Dimension	142(W) x 225(L) x 132(H)mm(Including rubber)
Weight	2.5kg(Including battery 3.2kg)
Viewing method and display	Two CMOS cameras and 4.3-inch color LCD monitor with touch screen
Fiber view and magnification	50X
Power supply	DC Lithium polymer battery(DC 14.8V, 8400mAh), 100~240V AC Adapter
N°. of splice/heating per battery full charge	320 cycle
Electrode life	More than 1,000 times
Terminals	USB, External power(DC 12V Available for car cigar jack)

STANDARD PACKAGE

CATEGORY	MODEL	QUANTITY
Arc Fusion Splicer	KR7	1
AC Adapter	F1-1	1
Sleeve Loader	S312	2
Spare Electrode	EI-22	1 pair
Battery Pack	S513	1
Alcohol Dispenser		1
Cooling Tray	CT-03(60mm)	1
Holder	H5-Series	1 pair
Tool Box	-	1
User Manual	-	1
Carrying Case	Hard Case	1

OPTION PACKAGE

CATEGORY	MODEL
Battery Pack	S513
Cleaver Blade	BI-05
Electrode	EI-22
Fiber Holder	H5-12, H5-10, H5-8, H5-6, H5-4, H5-2, H5-250, H5-900, H5-IN, H5-2.5
Sleeve	R-F40(40mm)
Sleeving Clamp	SC-01
External Power	DC 12V Available for car cigar jack