

➔ Specifications

Parameter	Specification
Operating Wavelength Range	1060-1070 nm
Insertion Loss	2.0 dB
Isolation	23 dB
Return Loss	50 dB
Cross Talk	45 dB
Maximum Power	300 mW
Fiber Tensile Load	5 N
PDL	0.2 dB
Operating Temperature	0° C ~ + 65° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	35 mm x 8.4 mm x 8.4 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications upon request.

Note3: Fiber type HI 1060 fiber.

➔ Ordering Information

C	I	R	-	106	-	03	-	A	-	L	-	0	7
				Center Wavelength		Ports		Fiber Length		Pigtail Style		Connector	
				106: 1064 nm		03: 3 ports		A: 1 meter		(=Package style)		0: None	7: LC/UPC
										B: bare fiber		1: FC/PC	8: LC/SPC
										L: 900 μm loose tube		2: FC/APC	9: Special
												3: SC/PC	A: FC/UPC
												4: SC/APC	B: SC/UPC
												5: FC/SPC	C: ST
												6: SC/SPC	



WAVETEL PARIS | RENNES | LARMOR-PLAGE | LANNION
 sales@wavetel.fr - www.wavetel.fr - +33(0)2 99 14 69 65