

Parameter		Type 1	Type 2	Type 3
Central Wavelength			1064 nm	
Band Width (-0.5 dB)		± 1.0 nm	± 2.5 nm	± 4.0 nm
Insertion Loss			≤ 1.0 dB	
Stop Band Wavelength Range		1000-1059 nm & 1069-1100 nm	1000-1053 nm & 1075-1100 nm	
Stop Band Isolation			≥ 25 dB	
Return Loss			≥ 45 dB	
PDL			≤ 0.1 dB	
Maximum Power Handling			300 mW	
Operating Temperature			0° C ~ + 65° C	
Storage Temperature			- 40° C ~ + 85° C	
Package Dimensions	Bare Fiber (B)	5.5 mm (Φ) x 35 mm (L)		
	900 μm Loose Tube (L)	5.5 mm (Φ) x 40 mm (L)		

Note3: Fiber Type ---- HI 1060 fiber.

F	B	P										
			Filter Type	Center Wavelength	Fiber Length	Pigtail Style			Connector			
			1: Type 1	1064: 1064	A: 1 meter	(=Package style)			0: None	7: LC/UPC		
			2: Type 2			B: bare fiber			1: FC/PC	8: LC/SPC		
			3: Type 3			L: 900 μm loose tube			2: FC/APC	9: Special		
									3: SC/ PC	A: FC/UPC		
									4: SC/APC	B: SC/UPC		
									5: FC/SPC	C: ST		
									6: SC/SPC			