

# Isotropic measurement of electric fields

from 100 MHz to 60 GHz using the Field Meter FieldMan®

The probe detects electric fields from 100 MHz up to 60 GHz. This frequency range covers almost the entire range of high frequency communications, right up to directional radio and satellite links and is also suitable for measurements on radar systems. The probe's high linearity and sensitivity make it ideal for checking human safety limit values in the general public and occupational environments.

The probe's interface digitally transmits the measurement data to the base unit, which has no individual influence on the measured values and therefore does not need to be calibrated. Probe calibration is carried out at several frequencies. The calibration data is stored in the probe and is automatically taken into account during the measurement. If the frequency of the predominating field strength is known, a correction factor can additionally be applied to increase the measurement accuracy.

- › Isotropic (non-directional) measurement
- › Excellent sensitivity starting at 0.5 V/m
- › Wide True RMS range up to 61 V/m
- › Digital probe interface - no more meter calibration
- › Self-test of the probe interface with integrated sensor function test
- › Automatic offset correction, no zero adjustment required
- › Wide temperature range from -20 °C to +50 °C
- › Extremely low temperature response
- › High Immunity at 50/60 Hz
- › Calibration is performed up to 60 GHz and is accredited up to 18 GHz



# Specifications <sup>1</sup>

Product Features	
Frequency range <sup>2</sup>	100 MHz to 60 GHz Flat 0.5 to 400 V/m (CW)
Type of frequency response	0.5 to 61.4 V/m (True RMS) 58 dB
Measurement range (nom.)	1600 V/m 66 nW/cm <sup>2</sup> to 42 mW/cm <sup>2</sup> (CW) 66 nW/cm <sup>2</sup> to 1.0 mW/cm <sup>2</sup> (True RMS)
Dynamic range (nom.)	1900 V/m
CW damage level (nom.)	Diode based system 700 mW/cm <sup>2</sup>
Peak damage level (nom.) <sup>3</sup>	Isotropic (Tri-axial) 1 W/cm <sup>2</sup>
Sensor type	Combined 3-axis (RSS)
Directivity	5 Hz / 275 ms
Spatial assessment	Integrated sensors for displaying the ambient temperature, for automatic offset compensation and for compensation of the temperature response
Sampling rate / integration time (nom.)	Interface function test and sensor test for interruption of diodes
Temperature sensors	
Self-test	

Uncertainty	
Flatness of frequency response <sup>4,5</sup> Calibration uncertainty not included	±3 dB (300 MHz to 40 GHz) +3/-6 dB (100 MHz to 60 GHz)
Linearity deviation (nom.) Referred to 0.2 mW/cm <sup>2</sup> (27.5 V/m)	±3 dB (1 to 2 V/m) ±1 dB (2 to 250 V/m) ±2 dB (250 to 400 V/m) ±3 dB (0.26 to 1 μW/cm <sup>2</sup> ) ±1 dB (1 μW/cm <sup>2</sup> to 16.5 mW/cm <sup>2</sup> ) ±2 dB (16.5 mW/cm <sup>2</sup> to 42 mW/cm <sup>2</sup> )
Isotropic deviation <sup>5</sup>	±1.25 dB (100 MHz to 10 GHz) ±2 dB (> 10 GHz to 26.5 GHz) ±2 dB typ. (> 26.5 GHz)
Temperature response (nom.) Referred to 0.2 mW/cm <sup>2</sup> (27.5 V/m) @ 2.45 GHz	±0.2 dB (-20 °C to +50 °C, related to 23 °C)

General Specifications		
Accredited calibration	DAkKS, ILAC-MRA (DIN EN ISO/IEC 17025, IEEE Std. 1309) For measurands outside the scope, a factory calibration is performed.	
Recommended calibration interval	24 months	
Operating temperature	-20 °C to +50 °C	
Humidity	< 29 g/m <sup>3</sup> (< 93 % RH at +30 °C), non-condensing	
Ingress protection	IP54 (probe screwed on)	
Climatic conditions	Storage	1K5 (IEC 60721-3) -40 °C to +70 °C
	Transport	2K4 (IEC 60721-3) -40 °C to +70 °C
	Operating	7K2 (IEC 60721-3) extended to -20 °C to +50 °C
Size	308 mm x 66 mm Ø	
Weight	< 100 g	
Country of origin	Germany	

<sup>1</sup> Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23±3 °C, relative air humidity 25% to 75%, sinusoidal signal, probe sampling rate 5 Hz.

<sup>2</sup> Cutoff frequency at typ. -6 dB.

<sup>3</sup> Pulse length 1 μsec, duty cycle 1:100.

<sup>4</sup> Frequency response can be compensated for by the use of correction factors stored in the probe memory.

<sup>5</sup> Results are calculated from the maximum and minimum response obtained during the full revolution about the stem of the probe, oriented 54.7° to the electric field vector.

# Definitions and Conditions

## Conditions

Unless otherwise noted, specifications apply after 30 minutes warm-up time within the specified environmental conditions. The product is within the recommended calibration cycle.

### Specifications with limits

These describe product performance for the given parameter covered by warranty. Specifications with limits (shown as <, ≤, >, ≥, ±, max., min.) apply under the given conditions for the product and are tested during production, considering measurement uncertainty.

### Specifications without limits

These describe product performance for the given parameter covered by warranty. Specifications without limits represent values with negligible deviations, which are ensured by design (e.g. dimensions or resolution of a setting parameter).

## Typical values (typ.)

These characterize product performance for the given parameter that is not covered by warranty. When stated as a range or as a limit (shown as <, ≤, >, ≥, ±, max., min.), they represent the performance met by approximately 80% of the instruments. Otherwise, they represent the mean value. The measurement uncertainty is not taken into account.

## Nominal values (nom.)

These characterize expected product performance for the given parameter that is not covered by warranty. Nominal values are verified during product development but are not tested during production.

## Uncertainties

These characterize the dispersion of the values attributed to the measurands with an estimated confidence level of approximately 95%. Uncertainty is stated as the standard uncertainty multiplied by the coverage factor k=2 based on the normal distribution. The evaluation has been carried out in accordance with the rules of the "Guide to the Expression of Uncertainty in Measurement" (GUM).

# Ordering Information

Digital Broadband Probe	Part number
Probe EFD-6091, E-Field, 100 MHz–60 GHz	2462/17

  

Optional Accessories	Part number
Cable, Digital Probe Extension, 2m <sup>6</sup>	2460/90.02

<sup>6</sup> The device specifications apply without an extension cable.

**Narda Safety Test Solutions GmbH**  
Sandwiesenstrasse 7  
72793 Pfullingen, Germany  
Phone +49 7121 97 32 0  
info@narda-sts.com

**Narda Safety Test Solutions**  
NorthAmerica RepresentativeOffice  
435 Moreland Road  
Hauppauge, NY11788, USA  
Phone +1 631 231 1700  
info@narda-sts.com

**Narda Safety Test Solutions S.r.l.**  
ViaBenessea 29/B  
17035 Cisano sul Neva, Italy  
Phone +39 0182 58641  
nardait.support@narda-sts.it

**Narda Safety Test Solutions GmbH**  
Beijing Representative Office  
Xiyuan Hotel, No. 1 Sanlihe Road, Haidian  
100044 Beijing, China  
Phone +86 10 6830 5870  
support@narda-sts.cn

www.narda-sts.com

® Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH - Trade names are trademarks of the owners.